

Product Description

HEUCOFLASH™ LQ2 is a nitrite free, highly effective, liquid flash rust inhibitor for all kind of waterborne protective coatings. The VOC free inhibitor can be used for all kind of water based protective coatings, metall treatment or packaging protection.

Appearance	Yellow liquid
------------	---------------

Technical Data

	Unit	Value	Test Method
Density	[g/cm ³]	typ. 1.1	
pH value		typ. 8.0	
Viscosity	[max. cps]	typ. 30	

Benefits



Control vs. a combination of an anticorrosive pigment and a liquid flash rust inhibitor in an APEO free, water based styrene acrylic primer.

Packaging and Handling

Packaging	30 kg plastic pail
Packaging	200 kg metal drum
Packaging	Different types of packaging are available on request
Storage	> 5 °C

Tds-ac_lq2-01_02

Disclaimer - The information given in this data sheet is based on the present state of our knowledge & is intended as a general description of our products & their possible applications. Neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Because of the multitude of formulations, production & application conditions, all the above mentioned data have to be adjusted to the circumstances of the processor. As customer use lies beyond our knowledge and control, we cannot accept any liability relating to the use of our products in any particular application. In addition to that, the legal rights of third parties must always be considered. No liabilities, including those for patent rights, can be derived from this fact for individual cases. It cannot be ruled out that this product contains particles < 0.1 µm. Any user of this product is responsible for determining the suitability of Sudarshan's products for its particular application & to ensure that any proprietary rights & existing laws & legislation are observed.